

Legacy “Fancy” Click Pen Kit

Available at www.thewoodturningstore.com

Assembly Instructions

Description:

The “Fancy” model is similar to the “Slimline” and is a great starter kit for those new to pen turning. The difference in Fancy Click Pen is the click mechanism instead of twist. Many experienced pen turners use the Fancy kit to make elaborate and unusual pens which vary greatly from the basic pen.

The Fancy pen uses two 7mm brass tubes of equal length. Both tubes are 2 1/32” long. Also, in the basic pen form, the wood blank is turned as a straight cylinder, which is simple and easier to turn than some of the more elaborate pens which require fairly precise curves to look good.

The Fancy pen is available in a wide range of finishes (Gold, Silver, Gun Metal, etc). You can also customize your Fancy pens with a wide variety of decorative pen clips.


Getting Started:

You will need the following accessories to make a Fancy Click pen. Many of these accessories can be used with other pen kits. (All accessories are available at www.thewoodturningstore.com)

- 1 wood or acrylic blank, approximately 5 inches long x 5/8” x 5/8”
- 7mm drill bit
- Woodturning pen mandrel with 7mm rod
- Slimline or Fancy pen bushing set
- Pen barrel trimmer (7mm)
- Glue (CA, epoxy or polyurethane [Gorilla])
- Lathe, turning tools, sandpaper, pen finish
- Other items may be needed as desired



Parts of the Fancy Click Pen Kit:



Preparing the Blank for Turning:

- Start with your wood or acrylic blank and cut it in half so you have 2 pieces, each about 2 ½” in length. Mark the blank with “hash marks” at the cut line so you can keep the grain matched when you mount the blanks on the pen mandrel.
- Using a 7mm twist drill, drill a hole through each blank. Be careful to drill slowly to avoid chipping and tearing the material. Also, it is highly recommended that you clamp the blank in a vise and use a drill press for the most accurate and straight hole. You could also mount each blank in a lathe chuck and drill the hole using your lathe.
- Roughen the surface of each brass tube with steel wool or fine sandpaper. Using one of the glues mentioned previously, glue the brass tube into the blank. Twist the tube when inserting it into the blank to insure good glue coverage. Center the tube in the blank, make sure the tube is at least 1/16” - 1/8” inside the blank so you can trim the blank end cleanly.
- Use a pen barrel trimmer (7mm) to square the ends of the blank to the brass tube. This is an important step which will create a clean line between the turned blank and the metal components of the pen kit.
- Your blanks are now ready to be mounted on the lathe.


Legacy “Fancy” Click Pen Kit

Available at www.thewoodturningstore.com

Assembly Instructions

Turning the blanks on the lathe

- Use a pen turning mandrel with a 7mm shaft and Slimline pen bushings (available at our store). You will need at least three bushings. For the slimline kit, the bushings are all the same diameter. Our pen mandrel kit includes 5 slimline bushings.
- Mount the pen blanks on the mandrel as shown in the diagram below. Make sure that your “hash marks” are in the center which assures that the grain of your blank will match that of the original single piece blank. Adjust the mandrel shaft so that the lock nut will tighten down on the assembly of pen blanks and bushings. Hand tighten the nut.
- Put a live center in your lathe’s tailstock and bring it in to support the mandrel shaft and keep it stable while turning.
- Using turning tools, turn the blanks to cylinders which are the diameter of the bushings.
- Note: Many turners prefer to turn the blank slightly oversize and then sand and polish the blank down to the exact size of the bushings.



Sanding, Polishing and Finishing the blank


- Most pens are finished to a high luster and finished with a durable coating of protective finish. Depending on your skill level and the material being used, you will need to sand with aluminum oxide paper of progressively finer grits, starting with a grit coarse enough to remove all tool marks and possibly shape the blank.
- If you have turned your piece oversize or if it is rough, you can smooth and even shape your blank with 80-100 grit sandpaper. Use a high lathe speed (2000+ RPM) but be careful not to overheat your piece which could cause heat checking.
- Progress through finer and finer grits 120, 180, 240, 320, 400, 600, etc.
- For acrylic materials you can use sandpaper up to 1000 grit then switch to micro mesh pads (up to 12000) and polishing cream to get a superior glossy finish.
- There are many finishes available for pens and you can experiment with what works best for you and the materials you use. Try to use a finish which will be durable and long lasting because the pen will be handled thousands of times and you want the finish to stay on and not be worn away (especially if you have sold the pen!)
- Remove the blanks from the pen mandrel and you are ready to assemble your pen.

Legacy “Fancy” Click Pen Kit




Available at www.thewoodturningstore.com

Assembly Instructions

Assembly of the Finished Pen:



- Now that you have turned and finished the blanks into the upper and lower halves, you are ready to assemble your pen.
- It is highly recommended that you use a vise or clamp to assemble the pen. It is essential that you press the parts together “straight”. If you press the parts together and they are not straight, they will not straighten as you continue to press. There are many commercially available pen presses which make the process simple and easy.
- Before you press the parts together, lay out your blanks so that you recall how the grain originally matched.
- First, press the click assembly with the clip into one end of the upper tube. Remember to watch for the original grain orientation.
- Next, press the center band into the other end of the upper tube.
- Press the other end of center band into one end of the lower tube. Then press the coupler into the other end of the lower tube.
- Slide the click mechanism through the lower end of the pen all the way up making sure you can see the threaded end of the click mechanism. Follow with the refill with spring then thread the tip onto the coupler.



- Insert the click spring onto the click assembly and thread the plunger. Note: Do not over tighten the assembly onto the click mechanism. Your pen is complete!
- To advance the refill press the end of the click mechanism, to retract the refill press the end of the click mechanism again.